

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 17/03/2014 Revision date: 13/01/2022 Supersedes version of: 30/07/2019 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : NST INOX flux cored wires
Synonyms : NST A-316L / A-309MoL / A-309L / A-308L/FCW A625 / 316LT/309MoLT / 309LT/308LT / 329J3L Duplex / NST 329J3L Duplex / NST 329J3L XLT Duplex

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Welding wire

Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Norsk Sveiseteknikk AS
Postboks 109, 3301 Hokksund
T + 47 99 27 80 00 - F + 47 32 82 90 19
Thomas@nst.no - nst.no

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Unit)	Claremont Place Newcastle-upon-Tyne, Newcastle	+44 191 2606182 +44 191 2606180	Hours of operation: 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Sens. 1 H317
Carc. 2 H351
STOT RE 1 H372

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains : Nickel
EUH-statements : EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
EUH210 - Safety data sheet available on request.
Extra phrases : Alloys in massive form do not need to be labeled acc. CLP Regulation (1272/2008), art. 23 (d) and Annex I 1.3.4.
These complex alloys in massive form have no known toxicological properties other than causing allergic reactions in individuals sensitive to the metals contained in the alloys. Hazardous fume or dust emissions may be released during remelting, grinding, cutting or welding.

2.3. Other hazards

Other hazards which do not result in classification : In the smoke emitted during use, there will be an additional risks if inhaled. Intensive exposure to welding fumes may cause lung disease, bronchitis, or worsen already existing inhalation problems. Intensified exposure to manganese (Mn) can damage the central nervous system or worsen existing health problems.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Iron	(CAS-No.) 7439-89-6 (EC-No.) 231-096-4	45 – 90	Not classified
Chromium	(CAS-No.) 7440-47-3 (EC-No.) 231-157-5	10 – 40	Not classified
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (EC Index-No.) 022-006-00-2 (REACH-no) 01-2119489379-17	5 – 15	Carc. 2, H351
Nickel (Note S)(Note 7)	(CAS-No.) 7440-02-0 (EC-No.) 231-111-4 (EC Index-No.) 028-002-00-7	5 – 15	Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372
Quartz (SiO ₂)	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4 (REACH-no) N/A	5 – 15	Not classified
Zirconium compounds (as Zr)	(CAS-No.) 1314-23-4 (EC-No.) 215-227-2 (REACH-no) 01-2119486976-14	3 – 9	Not classified
aluminium(III)oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6 (REACH-no) N/A	2 – 8	Not classified
Molybdenum	(CAS-No.) 7439-98-7 (EC-No.) 231-107-2 (REACH-no) 01-2119472304-43	< 4	Not classified
Manganese	(CAS-No.) 7439-96-5 (EC-No.) 231-105-1 (REACH-no) 01-2119449803-34	< 2.5	Not classified
silicon	(CAS-No.) 7440-21-3 (EC-No.) 231-130-8 (REACH-no) 01-2119480401-47	< 1.5	Not classified

Note 7 : Alloys containing nickel are classified for skin sensitisation when the release rate of 0,5 µg Ni/cm²/week, as measured by the European Standard reference test method EN 1811, is exceeded.

Note S : This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1).

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: General first aid, rest, warmth and fresh air. Move to fresh air. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell. Artificial respiration if indicated.
First-aid measures after skin contact	: Wash skin with soap and water. Get medical attention if irritation persists after washing. If burned, cool skin with ice or cold water.
First-aid measures after eye contact	: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues.
First-aid measures after ingestion	: Rinse nose, mouth and throat with water.

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Overexposure to welding fumes may affect pulmonary function. Strong exposure to manganese may affect the nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Electric shock: Disconnect and turn off the power. If the victim is conscious or has partial loss of consciousness, open the airways. If the breathing has stopped, give artificial respiration. If cardiac arrest, provide heart massage and artificial respiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Non flammable.

Hazardous decomposition products in case of fire : Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. Ozone. Oxides of: Iron. Manganese. Titanium. Silicon. Molybdenum (Mo). Boron (B). Chromium. Fluorine (F). Nickel (Ni).

5.3. Advice for firefighters

Protection during firefighting : Do not enter fire area without proper personal protective equipment, including respiratory protection (EN137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes. Do not breathe vapour.

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate personal protective equipment - see Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into drains.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Limit spread of spilled material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Mechanical ventilation or local exhaust ventilation is required. Do not breathe dust, fume, vapours. Avoid contact with skin and eyes. Do not touch electrical parts, such as welding wire and welding machine terminals. Wear appropriate personal protective equipment - see Section 8.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place.

Incompatible materials : Acids. Moisture.

Storage temperature : 17 – 25 °C

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional data.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Manganese (7439-96-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Manganese and its inorganic compounds
WEL TWA (OEL TWA) [1]	0.2 mg/m ³ Inhalable fraction (as Mn) 0.05 mg/m ³ Respirable fraction (as Mn)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Iron (7439-89-6)	
United Kingdom - Occupational Exposure Limits	
Local name	Iron salts
WEL TWA (OEL TWA) [1]	1 mg/m ³ (as Fe)
WEL STEL (OEL STEL)	2 mg/m ³ (as Fe)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Chromium (7440-47-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Chromium
WEL TWA (OEL TWA) [1]	0.5 mg/m ³ 0.5 mg/m ³ Chromium (II) compounds (as Cr) 0.5 mg/m ³ Chromium (III) compounds (as Cr)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Chromium VI
BMGV	10 µmol/mol creatinine Parameter: chromium - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Molybdenum (7439-98-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Molybdenum
WEL TWA (OEL TWA) [1]	10 mg/m ³ insoluble compounds (as Mo) 5 mg/m ³ soluble compounds (as Mo)
WEL STEL (OEL STEL)	20 mg/m ³ insoluble compounds (as Mo) 10 mg/m ³ soluble compounds (as Mo)

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
----------------------	---------------------------------------

Nickel (7440-02-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Nickel
WEL TWA (OEL TWA) [1]	0.1 mg/m ³ and its inorganic compounds (except nickel tetracarbonyl): water-soluble nickel compounds (as Ni) 0.5 mg/m ³ and its inorganic compounds (except nickel tetracarbonyl): nickel and water insoluble nickel compounds (as Ni)
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), Carc (Capable of causing cancer and/or heritable genetic damage (nickel oxides and sulphides)), Sen (Capable of causing occupational asthma (nickel sulphate))
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Zirconium compounds (as Zr) (1314-23-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Zirconium
WEL TWA (OEL TWA) [1]	5 mg/m ³ compounds (as Zr)
WEL STEL (OEL STEL)	10 mg/m ³ compounds (as Zr)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

aluminium(III)oxide (1344-28-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

silicon (7440-21-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Silicon
WEL TWA (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Exposure limit values for the other components

ironoxide (1309-37-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Iron oxide
WEL TWA (OEL TWA) [1]	5 mg/m ³ fume (as Fe)
WEL STEL (OEL STEL)	10 mg/m ³ fume (as Fe)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Aluminium sveiserøyk	
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Aluminium sveiserøyk		
WEL TWA (OEL TWA) [1]	2 mg/m ³ alkyl compounds 2 mg/m ³ salts, soluble 10 mg/m ³ metal, inhalable dust 4 mg/m ³ metal, respirable dust	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide eyewash station. Working operations which cause formation of high volumes of vapour should take place in ventilation hood or with local exhaust ventilation. It is forbidden to weld in rooms where there are halogenated solvents in the working atmosphere.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Use approved safety goggles or face shield. Wear safety glasses with high protection against UV radiation. STANDARD EN 166.

8.2.2.2. Skin protection

Skin and body protection:

Wear thermal insulated gloves, shoes and other safety equipment designed for welding

Hand protection:

Gloves made of insulating material. Heat-resistant gloves. EN 388:2016. Chemical resistant gloves required for prolonged or repeated contact. STANDARD EN 374.

Other skin protection

Materials for protective clothing:

Heatproof clothing

8.2.2.3. Respiratory protection

Respiratory protection:

During welding supplied-air respirator or motor assisted respirators with P2 or P3-filter should be used in combination with brown, yellow and gray gas filter. Respiratory protection should be used in conjunction with welding hood. Standard EN 143:2021. STANDARD EN 149. EN 405. EN 139

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: According to product specification.
Appearance	: Wire.
Odour	: Odourless or no characteristic odour.
Odour threshold	: Not relevant.

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Melting point	: Not determined.
Freezing point	: Not relevant.
Boiling point	: Not relevant.
Flammability	: Not applicable
Explosive properties	: Not explosive.
Oxidising properties	: Non flammable.
Explosive limits	: Not relevant.
Lower explosive limit (LEL)	: Not applicable
Upper explosive limit (UEL)	: Not applicable
Flash point	: Not relevant.
Auto-ignition temperature	: Not relevant.
Decomposition temperature	: Not relevant.
pH	: Not relevant.
pH solution	: Not available
Viscosity, kinematic	: Not relevant.
Viscosity, dynamic	: Not relevant.
Solubility	: Not soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water (Log Pow)	: Not determined.
Vapour pressure	: Not relevant.
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not determined.
Relative vapour density at 20 °C	: Not relevant.
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1)	: Not relevant.
Additional information	: None to our knowledge.

SECTION 10: Stability and reactivity

10.1. Reactivity

No incompatible groups noted.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Will not polymerise.

10.4. Conditions to avoid

Water, humidity.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

The most ordinary chimney gases include: Ozone. Carbon dioxide. Carbon monoxide. Oxides of: boron. Chromium. Iron. Fluorides. Manganese. Molybdenum (Mo). Nickel (Ni). Silicon (Si). Titanium.

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Manganese (7439-96-5)	
LD50 oral rat	9000 mg/kg

Iron (7439-89-6)	
LD50 oral rat	30000 mg/kg

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l/4h

Nickel (7440-02-0)	
LD50 oral rat	> 5000 mg/kg

Zirconium compounds (as Zr) (1314-23-4)	
LD50 oral rat	> 8800 mg/kg

aluminium(III)oxide (1344-28-1)	
LD50 oral rat	> 5000 mg/kg

silicon (7440-21-3)	
LD50 oral rat	3160 mg/kg

Skin corrosion/irritation	: Not classified pH: Not relevant.
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified pH: Not relevant.
Additional information	: Dust from this product may cause eye irritation Vapor may irritate eyes
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.
Additional information	: Prolonged and repeated inhalation of welding fumes may cause an increased risk of developing lungrelated cancers.
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: In the smoke emitted during use, there will be an additional risks if inhaled. Intensive exposure to welding fumes may cause lung disease, bronchitis, or worsen already existing inhalation problems. Intensified exposure to manganese (Mn) can damage the central nervous system or worsen existing health problems. Inhalation of fumes or vapours may cause respiratory irritation
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.

Nickel (7440-02-0)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

NST INOX flux cored wires	
Viscosity, kinematic	Not relevant.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2 Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Manganese (7439-96-5)	
LC50 - Fish [1]	2.91 mg/l (96 hours)
EC50 - Crustacea [1]	5.2 mg/l 48 hours
EC50 72h - Algae [1]	0.55 mg/l

Iron (7439-89-6)	
LC50 - Fish [1]	13.6 mg/l 96h (FeCl ₂) Morone saxatilis
EC50 - Crustacea [1]	5.2 mg/l 48h

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LC50 - Fish [1]	> 1000 mg/l Fundulus heteroclitus
EC50 - Crustacea [1]	> 1000 mg/l (48 hours - Daphnia magna)

Molybdenum (7439-98-7)	
LC50 - Fish [1]	2600 mg/l LC50 96 h - fish [mg/l]

Nickel (7440-02-0)	
LC50 - Fish [1]	> 100 mg/l (96 hours - Brachydanio rerio, zebra-fish)
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna, 48 hours

aluminium(III)oxide (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l LC50 96h fish Salmo trutta
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna, 48 hours

12.2. Persistence and degradability

NST INOX flux cored wires	
Persistence and degradability	The product is not biodegradable.

Iron (7439-89-6)	
Persistence and degradability	There are no data on the degradability of this product.

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

12.3. Bioaccumulative potential

NST INOX flux cored wires	
Partition coefficient n-octanol/water (Log Pow)	Not determined.
Bioaccumulative potential	No data available on bioaccumulation.

Manganese (7439-96-5)	
Bioconcentration factor (BCF REACH)	59052

Iron (7439-89-6)	
Bioconcentration factor (BCF REACH)	140000

Nickel (7440-02-0)	
Bioconcentration factor (BCF REACH)	16
Partition coefficient n-octanol/water (Log Pow)	< 0

12.4. Mobility in soil

NST INOX flux cored wires	
Ecology - soil	The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

NST INOX flux cored wires	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

Component	
Iron (7439-89-6)	This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : None to our knowledge.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Dispose as hazardous waste.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a hazardous or special waste collection point.
European List of Waste (LoW) code : 12 01 13 - welding wastes

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

Safety Data Sheet

NST INOX flux cored wires

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:

Carc. 2	Carcinogenicity, Category 2
EUH210	Safety data sheet available on request.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1

The information in this safety data sheet is based on information from the manufacturer/supplier, present European and national legislation, and presupposes that the product is used within the specified area of application.