NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II) Issue date: 17/12/2020 Revision date: 17/12/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NSWE SF-80 A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use Use of the substance/mixture : Welding wire

Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Norsk Sveiseteknikk AS Postboks 109, 3301 Hokksund T + 47 99 27 80 00 - F + 47 32 82 90 19

Thomas@nst.no - nst.no

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Unit)	Claremont Place Newcastle-upon-Tyne, Newcastle	+44 191 2606182 +44 191 2606180	Hours of operation: 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

 Skin Sens. 1
 H317

 Carc. 2
 H351

 STOT RE 2
 H373

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Alloy. According to EC directives or the corresponding national regulations there is no labelling obligation for this product.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

2.3. Other hazards

Other hazards which do not result in classification

: In the smoke emitted by use, there will be am additional risks if inhaled. Intensive exposure to welding fumes may cause lung disease, bronchitis, or worsen already existing inhalation problems. Intensified exposure to manganese (Mn) can damage the central nervous system or worsen existing health problems.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Iron	(CAS-No.) 7439-89-6 (EC-No.) 231-096-4	< 100	Not classified
titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	< 10	Carc. 2, H351



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Manganese	(CAS-No.) 7439-96-5 (EC-No.) 231-105-1 (REACH-no) 01-2119449803-34	< 5	Not classified
Nickel (Note S)(Note 7)	(CAS-No.) 7440-02-0 (EC-No.) 231-111-4 (EC Index-No.) 028-002-00-7	< 5	Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372
silicon	(CAS-No.) 7440-21-3 (EC-No.) 231-130-8 (REACH-no) 01-2119480401-47	< 1	Not classified
silicondioxide, amorphous	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4 (REACH-no) N/A	< 1	Not classified
magnesium (Note T)	(CAS-No.) 7439-95-4 (EC-No.) 231-104-6 (EC Index-No.) 012-002-00-9 (REACH-no) 01-2119537203-49	< 1	Pyr. Sol. 1, H250 Water-react. 1, H260
alkali fluorosilicates(K) (Note A)	(CAS-No.) 16871-90-2 (EC-No.) 240-896-2 (EC Index-No.) 009-012-00-0	< 1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301
Copper	(CAS-No.) 7440-50-8 (EC-No.) 231-159-6 (REACH-no) 01-2119480154-42	< 1	Aquatic Chronic 2, H411

Note 7 : Alloys containing nickel are classified for skin sensitisation when the release rate of 0,5 µg Ni/cm2/week, as measured by the European Standard reference test method EN 1811, is exceeded.

Note A: Without prejudice to Article 17(2), the name of the substance must appear on the label in the form of one of the designations given in Part 3. In Part 3, use is sometimes made of a general description such as '... compounds' or '... salts'. In this case, the supplier is required to state on the label the correct name, due account being taken of section 1.1.1.4.

Note S: This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of H-statements: see section 16

SECTION 4: First aid measures

41	Description	of firet	hic	maggurag
4.1.	Describition	OI IIISL	aıu	IIIeasures

First-aid measures general : General first aid, rest, warmth and fresh air. Move to fresh air. Call a poison center or a

doctor if you feel unwell.

First-aid measures after inhalation : Move to fresh air. Call a POISON CENTER/doctor if you feel unwell. Artificial respiration if

indicated.

First-aid measures after skin contact : Wash skin with soap and water. Get medical attention if irritation persists after washing. If

burned, cool skin with ice or cold water.

First-aid measures after eye contact : Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses

and open eyes wide apart. Get medical attention if any discomfort continues.

First-aid measures after ingestion : Rinse nose, mouth and throat with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Overexposure to welding fumes may affect pulmonary function. Strong exposure to

manganese may affect the nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Electric shock: Disconnect and turn off the power. If the victim is conscious or has partial loss of consciousness, open the airways. If the breathing has stopped, give artificial respiration. If cardiac arrest, provide heart massage and artificial respiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Foam, carbon dioxide or dry

powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Non flammable.

Hazardous decomposition products in case of fire : Hazardous decomposition products may be released during prolonged heating like

smokes, carbon monoxide and dioxide. Oxides of: Iron. Manganese. Titanium. copper. Silicon. Nickel (Ni).



According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

5.3. Advice for firefighters

Protection during firefighting : Do not enter fire area without proper personal protective equipment, including respiratory

protection (EN137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes. Do not breathe vapour.

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate personal protective equipment - see Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into drains.

6.3. Methods and material for containment and cleaning up

: Collect spillage. Limit spread of spilled material. Collect spillage in containers, seal For containment

securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Mechanical ventilation or local exhaust

ventilation is required. Avoid breathing vapours, fume. Avoid contact with skin and eyes. Do not touch electrical parts, such as welding wire and welding machine terminals.

: Wash hands and other exposed areas with mild soap and water before eating, drinking or Hygiene measures

smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place.

7.3. Specific end use(s)

No additional data.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

silicon (7440-21-3)		
United Kingdom	Local name	Silicon
United Kingdom	WEL TWA (OEL TWA) [1]	10 mg/m³ inhalable dust 4 mg/m³ respirable dust
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

magnesium (7439-95-4)		
United Kingdom	Local name	Magnesium oxide
United Kingdom	WEL TWA (OEL TWA) [1]	4 mg/m³ (as Mg) fume and respirable dust 10 mg/m³ (as Mg) inhalable dust fume
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

titanium dioxide (13463-67-7)		
United Kingdom	Local name	Titanium dioxide
United Kingdom	WEL TWA (OEL TWA) [1]	4 mg/m³ respirable 10 mg/m³ total inhalable
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Nickel (7440-02-0)		
United Kingdom	Local name	Nickel
United Kingdom	WEL TWA (OEL TWA) [1]	0.1 mg/m³ and its inorganic compounds (except nickel tetracarbonyl): water-soluble nickel compounds (as Ni) 0.5 mg/m³ and its inorganic compounds (except nickel tetracarbonyl): nickel and water insoluble nickel compounds (as Ni)
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), Carc (Capable of causing cancer and/or heritable genetic damage (nickel oxides and sulphides)), Sen (Capable of causing occupational asthma (nickel sulphate))
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Copper (7440-50-8)		
United Kingdom	Local name	Copper
United Kingdom	WEL TWA (OEL TWA) [1]	0.2 mg/m³ fume (as Cu) 1 mg/m³ and compounds, dusts and mists (as Cu)
United Kingdom	WEL STEL (OEL STEL)	2 mg/m³ and compounds, dusts and mists (as Cu)
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Exposure limit values for the other components

ironoxide (1309-37-1)			
United Kingdom	Local name	Iron oxide	
United Kingdom	WEL TWA (OEL TWA) [1]	5 mg/m³ fume (as Fe)	
United Kingdom	WEL STEL (OEL STEL)	10 mg/m³ fume (as Fe)	
United Kingdom	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide eyewash station. Working operations which cause formation of high volumes of vapour should take place in ventilation hood or with local exhaust ventilation. It is forbidden to weld in rooms where there are halogenated solvents in the working atmosphere.

Materials for protective clothing:

Heatproof clothing

Hand protection:

Gloves made of insulating material. Heat-resistant gloves. EN 388:2016. Chemical resistant gloves required for prolonged or repeated contact. STANDARD EN ISO 374-1:2016/A1:2018, EN ISO 374-2:2019, EN ISO 374-4:2019

Eye protection:

Use approved safety goggles or face shield. Wear safety glasses with high protection against UV radiation. STANDARD EN 166:2001

Skin and body protection:

Heatproof clothing. Heat-resistant glopves.

Respiratory protection:

During welding supplied-air respirator or motor assisted respirators with P2 or P3-filter should be used in combination with brown, yellow and gray gas filter. Respiratory protection should be used in conjunction with welding hood. Standard EN 143. STANDARD EN 149:2001 + A1:2009. EN 405. FN 139

Other information:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Wire.
Colour : Metal. copper.



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

: Odourless. Odour Odour threshold : Not relevant. рΗ : Not relevant. Relative evaporation rate (butylacetate=1) : Not relevant. : Not determined. Melting point Freezing point Not determined Boiling point : Not relevant. Flash point : Not relevant. Auto-ignition temperature : Not determined. Decomposition temperature : Not determined. Flammability (solid, gas) : Not applicable Vapour pressure : Not relevant. Relative vapour density at 20 °C : Not relevant. Relative density : Not determined. Solubility : Not soluble in water. Partition coefficient n-octanol/water (Log Pow) : Not determined. Viscosity, kinematic : Not relevant. Viscosity, dynamic : Not relevant. Explosive properties : Not explosive. Oxidising properties : Non flammable. Explosive limits : Not relevant.

9.2. Other information

Additional information : None to our knowledge.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Will not polymerise.

10.4. Conditions to avoid

Water, humidity.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

Carbon dioxide. Ozone. Oxides of: Iron. Manganese. Titanium. copper. Silicon (Si).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Manganese	(7439-96-5
-----------	------------

LD50 oral rat 9000 mg/kg

silicon (7440-21-3)

LD50 oral rat 3160 mg/kg

titanium dioxide (13463-67-7)		
	LD50 oral rat	> 10000 mg/kg
	LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l/4h



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Skin corrosion/irritation : Not classified

pH: Not relevant.

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified

pH: Not relevant.

Additional information : Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Suspected of causing cancer.

Additional information : Contains a substance which is (possibly) carcinogenic

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified

Additional information : In the smoke emitted by use, there will be am additional risks if inhaled. Intensive exposure

to welding fumes may cause lung disease, bronchitis, or worsen already existing inhalation problems. Intensified exposure to manganese (Mn) can damage the central nervous

system or worsen existing health problems.

Inhalation of fumes or vapours may cause respiratory irritation

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

NSWE SF-80 A	
Viscosity, kinematic	Not relevant.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

: Not classified

Manganese (7439-96-5)	
LC50 - Fish [1]	2.91 mg/l (96 hours)
EC50 - Crustacea [1]	5.2 mg/l 48 hours

silicondioxide, amorphous (14808-60-7)	
LC50 - Fish [1]	(96 hours - Brachydanio rerio, zebra-fish)
EC50 - Crustacea [1] 7600 mg/l (48 hours - Daphnia magna)	
ErC50 algae 440 mg/l (EC50, 72 hours - Selenastrum capricornutum)	

titanium dioxide (13463-67-7)	
LC50 - Fish [1]	> 1000 mg/l Fundulus heteroclitus
EC50 - Crustacea [1]	> 1000 mg/l (48 hours - Daphnia magna)

12.2. Persistence and degradability

NSWE SF-80 A	
Persistence and degradability	The product is not biodegradable.

12.3. Bioaccumulative potential

NSWE SF-80 A	
Partition coefficient n-octanol/water (Log Pow)	Not determined.
Bioaccumulative potential	No data available on bioaccumulation.



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Manganese (7439-96-5)	
Bioconcentration factor (BCF REACH)	59052

silicondioxide, amorphous (14808-60-7)	
Partition coefficient n-octanol/water (Log Pow)	0.53

12.4. Mobility in soil

NSWE SF-80 A	
Ecology - soil	The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

NSWE SF-80 A This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects : None to our knowledge.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Product is not hazardous waste.

Waste treatment methods : Do not discharge into drains.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

European List of Waste (LoW) code : 12 01 13 - welding wastes

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID	
14.1. UN number	14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.2. UN proper shipping name	14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.3. Transport hazard class(e	14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.4. Packing group	14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.5. Environmental hazards					
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
No supplementary information available					

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated



NSWE SF-80 A

According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Contains no substance on the REACH candidate list

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition

regulations

: EC-regulation 2015/830 /EC, 1907/2006/EC (REACH), 1272/2008/EC (CLP), 790/2009/EC. Transport of dangerous goods (ADR/RID, IMDG, IATA/ICAO). Workplace

exposure limits.

National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

SDS ID : 305296

Data sources : EC-regulation 2015/830 /EC, 1907/2006/EC (REACH), 1272/2008/EC (CLP), 790/2009/EC. Transport of

dangerous goods (ADR/RID, IMDG, IATA/ICAO). Workplace exposure limits.

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Carc. 2	Carcinogenicity, Category 2	
Pyr. Sol. 1	Pyrophoric Solids, Category 1	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1	
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2	
Water-react. 1	Substances and Mixtures which, in contact with water, emit flammable gases, Category 1	
H250	Catches fire spontaneously if exposed to air.	
H260	In contact with water releases flammable gases which may ignite spontaneously.	
H301	Toxic if swallowed.	
H311	Toxic in contact with skin.	
H317	May cause an allergic skin reaction.	
H331	Toxic if inhaled.	
H351	Suspected of causing cancer.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	

